

06

Pryžová kola

Rubber Wheels



Valivý odpor	Rolling Resistance	■ ■ ■ ■ ■ ■ ■ ■
Otočný odpor	Swivel Resistance	■ ■ ■ ■ ■ ■ ■ ■
Tlumení	Shock Absorbing	■ ■ ■ ■ ■ ■ ■ ■
Hlučnost	Noise	■ ■ ■ ■ ■ ■ ■ ■

Otěruvzdornost	Abrasion Resistance	■ ■ ■ ■ ■ ■ ■ ■
Odolnost proti trhání	Tearing Resistance	■ ■ ■ ■ ■ ■ ■ ■
Šetrnost k povrchu	Floor Friendliness	■ ■ ■ ■ ■ ■ ■ ■
Tvarová stálost	Shape Stability	■ ■ ■ ■ ■ ■ ■ ■

Pryžová kola typu 06Jr

Rubber Wheels Type 06Jr



Materiál disku	polypropylen
Uložení	jedno kuličkové ložisko
Krytka	polyamid
Materiál běhounu	termoplastická pryž
Tvrдость běhounu	65 ShA
Bezestopý běhoun	Ano
Typ ovládání	strojní
Max. rychlost	4 km/h
Pasivní teplotní odolnost	od -25°C do 80°C

Wheel centre material	polypropylene
Bearing	single ball bearing
Threadguard	polyamide
Tread material	thermoplastic rubber
Tread hardness	65 ShA
Non marking tread	Yes
Control type	powered
Max. speed	4 km/h
Passive temp. resistance	from -25°C to 80°C



	mm	mm	mm	mm	kg
06J080r-46-08	80	32	46	8	90
06J100r-46-08	100	32	46	8	100
06J125r-46-08	125	32	46	8	120
06J160r-60-12	160	40	60	12	180
06J200r-60-12	200	40	60	12	220

ESD pryžová kola typu 06Ja

ESD Rubber Wheels Type 06Ja

ESD



Materiál disku	polypropylen
Uložení	jedno kuličkové ložisko
Krytka	polyamid
Materiál běhounu	termoplastická pryž
Tvrдость běhounu	65 ShA
Bezestopý běhoun	Ano
Typ ovládání	strojní
Max. rychlost	4 km/h
Pasivní teplotní odolnost	od -25°C do 80°C
El. odpor	1000000 Ohm

Wheel centre material	polypropylene
Bearing	single ball bearing
Threadguard	polyamide
Tread material	thermoplastic rubber
Tread hardness	65 ShA
Non marking tread	Yes
Control type	powered
Max. speed	4 km/h
Passive temp. resistance	from -25°C to 80°C
El. Resistance	1000000 Ohm



	mm	mm	mm	mm	kg
06J080a-46-08	80	32	46	8	90
06J100a-46-08	100	32	46	8	100
06J125a-46-08	125	32	46	8	120
06J160a-60-12	160	40	60	12	200
06J200a-60-12	200	40	60	12	225